Full-Wave Effects in Coronagraph Masks



Jet Propulsion Laboratory California Institute of Technology Pasadena, California


Daniel. J. Hoppe
Thomas A. Cwik
Jet Propulsion Laboratory
4800 Oak Grove Drive
Pasadena, CA 91109

This research was carried out at the Jet Propulsion Laboratory, California Institute of Technology, under a contract with the National Aeronautics and Space Administration.

Fourier Optics Analysis of Thin Masks




Jet Propulsion Laboratory California Institute of Technology Pasadena, California



Incident Field (Airy Disk)

Spectrum

 $\widetilde{A}_i(k_x,k_y)$




Assumes T(x,y) is
Independent of $A_i(x,y)$, Independent of λ ,
Independent of Polarization ...!
[For Binary Masks T(x,y)=1/0]


Fourier Transform of ${\bf A}_0$ is equivalent to the far field radiated toward the Lyot stop.

$$\widetilde{A}_{o}(k_{x},k_{y}) = \widetilde{A}_{i}(k_{x},k_{y}) \otimes \widetilde{T}(k_{x},k_{y})$$

A convolution only for the simple T(x,y) behavior assumed above!



Binary Image-Plane Mask




Pupil-Plane Masks

Full-Wave Electromagnetic Effects in Thick Masks



California Institute of Technology Pasadena, California



- Finite Conductivity of the Metal Layer
- Thickness of the Metal Layer [Due to Finite Conductivity]
- Dependence of the Transmission Coefficient on the Polarization of the Incident Field
- Dependence of the Transmission Coefficient on the Illumination Angle of the Incident Field
- Interaction Between Different Regions/Periods of the Mask
- Substrate Effects

Full-Wave Analysis of Masks



Jet Propulsion Laboratory California Institute of Technology Pasadena, California

- Typical dimensions for a single period of the smallest structure of interest, a Sin² binary image plane mask: For F/15 (considered a minimum): $T_x=150\lambda$, $T_y=15\lambda$, and Thickness=0.6 λ . [Large EM Problem!]
- Goals
 - Estimate the smallest acceptable F# for the binary image-plane masks to function properly [smallest allowable feature sizes?]
 - Estimate cross-polarization levels introduced by the masks
 - Estimate bandwidth effects/limitations
- Two-Pronged Approach
 - Pursue exact analysis using available solution techniques: GTD/UTD, FDTD, MOM, FMM, ...
 - Consider several types of approximate analysis
 - Obtain order-of-magnitude estimates for EM effects
 - Use in "Local", approximate analysis of a real mask
 - Compare various mask types against each other
 - Example problems
 - Canonical Problem: thick periodic gratings
 - Approximate propagation through thick apertures using modal expansion

Thick Periodic Grating




Pasadena, California

- Why a Thick Periodic Grating?
 - Thick One-Dimensional Grating will Demonstrate Propagation
 Effects of Gap Size and Incident Polarization
 - Periods of 30-100l (F# =30-100) Translate into a Reasonable EM
 Problem for which a Converged Result can be Obtained
 - Both the Periodic and Non-Periodic Binary Masks Appear as A
 Thick Periodic Grating when Examined Locally and will Share
 many of the Grating's EM Effects
 - Grating Transmission Coefficients can be used in an Approximate Analysis of the Binary Mask


Canonical Example: Thick Strip Grating, Relative Transmission Versus Gap Dimension, 30λ Period



Jet Propulsion Laboratory California Institute of Technology Pasadena, California




Perpendicular Polarization




Parallel Polarization

Relative Transmission (0.6 lambda Thick Strip Array, Period=30 lambda)



Relative Transmission (0.6 lambda Thick Strip Array, Period=30 lambda)



Approximate Mask Performance Using Parallel Plate Transmission Coefficients in

National Aeronautics and Space Administration


Pasadena, California


Binary Sin² Mask

Jet Propulsion Laboratory
California Institute of Technology

the Gaps

Smallest Gap





Relative Amplitude

Relative Phase


F/15 Approximate Transmission Coefficients

Approximate Lyot Stop Fields F/15 Contrast @ $5\lambda/D \approx 60 \text{ dB}$ Other Polarization (not shown) $\approx 68 \text{ dB}$ F/30 Results $\approx 69/80 \text{ dB}$


Approximate Propagation Through a Thick Aperture



Jet Propulsion Laboratory
California Institute of Technology
Pasadena, California



Example Aperture Mode Sin² Binary Mask





- Determine Waveguide Modes of the Aperture (analytic/FEM)
- Expand Incident Electric Field Into This Modes Set
- Ignore Magnetic Field
- Propagate/Decay Modes Through the Aperture
- Evaluate Field at Aperture Exit
- Estimates: Phase and Amplitude Throughout Aperture and Cross-Polarization
- Exact Solution Adds Magnetic Field Match and Reflected Modes in Aperture


Analytic Example: Sector-Shaped Aperture, p-Directed Incident Field




Jet Propulsion Laboratory California Institute of Technology Pasadena, California











Example Modes






Small-Scale Example Binary Sin² Mask



Jet Propulsion Laboratory California Institute of Technology Pasadena, California



Single Cell of 2-D Periodic Structure Must Transform to Find Lyot Stop Fields

- Small Scale Example (F/3), Illustrates Full-Wave Effects
- Aperture Size 30λx3λ
- Thickness 0.6λ
- Y (Perpendicular) Polarization
- FEM Solution/Modal Expansion into 300 Waveguide Modes
- Visible Effects:
 - High-Order Phase/Amplitude Ripple [OK if Rapid Enough]
 - Distortion/Shorting of Field Near PEC Edges [Effective Area]
 - Cross Polarized Field Near
 Internal Corners (not shown here)
- This Work is On-Going